



KRAUS PREMIUM ADHESIVE

vinyl plank, tile and sheet

Tec 1.0 Ultimate Vinyl Adhesive



TEC 1.0 Ultimate Vinyl Adhesive combats the flooring industry's toughest challenge – wet slabs and high alkalinity. TEC 1.0 brings to the flooring contractor advanced technology to handle concrete substrates with a high moisture vapor emission rate, MVER, and sub-floor relative humidity, RH, without the need for moisture mitigation coatings. The TEC 1.0 is a one-step, high performance adhesive formulated for installing vinyl sheet, rubber tile, rubber sheet*, and LVT over both porous and non-porous sub-floors.

Size	Trowel Sizes/Spread Rate
4 Gallon	180-250 sq. ft./gallon

KPA 202 Fiberglass Sheet Vinyl Adhesive



KPA 202 is a high quality, acrylic based adhesive for fiberglass sheet vinyl. Its pressure sensitive qualities allow for easy repair and removal of flooring. KPA 202's fast drying, non-staining characteristics allow for fast carefree installations. It is CRI Green Label Plus certified, has 24 hour working time and is BioFresh® antimicrobial protected.

Size	Trowel Sizes/Spread Rate
4 Gallon	1/16" x 1/32" x 1/32" U-Notch, 180-250 sq. ft./gallon
1 Gallon	3/8" x 1/16" x 1/16" Square, 125-150 sq. ft./gallon

KPA 501 Vinyl Tile and Plank Adhesive



KPA 501 is an acrylic based adhesive specifically formulated for installing solid vinyl plank, tile and LVT. It may also be used to install solid vinyl sheet flooring, PVC backed broadloom and carpet tiles. It is moisture and alkali resistant and forms a tenacious, permanent bond. KPA 501 has excellent plasticizer migration resistance. This CRI Green Label Plus, zero VOC adhesive is protected by the BioFresh® antimicrobial protected.

Size	Trowel Sizes/Spread Rate
4 Gallon	Mineral/Paper backed:
1 Gallon	1/16" x 1/16" x 1/16" Square, 125-150 sq. ft./gallon
	Solid Vinyl/PVC:
	1/16" x 1/16" x 1/16" Square, 125-150 sq. ft./gallon

KRAUS PREMIUM ADHESIVE

vinyl tile and plank



KPA 204 Fiberglass Core Sheet Vinyl Seam Adhesive

KPA 204 Vinyl Seam Adhesive is an acrylic copolymer based adhesive specifically formulated for seaming sheet vinyl with fiberglass cores. KPA 204 is warranted for the seaming of Verity Sheet Vinyl and other similar products. Like all of our adhesives, this adhesive is protected by the CleanGuard R two-stage antimicrobial.

Size	Trowel Sizes/Spread Rate
1 Pint	100-150 sq. ft./16 oz bottle



KPA 505 Floor Primer

KPA 505 primer is specially formulated as a primer coat over common sub-floors; concrete, APA approved plywood underlayment, floor patch, self-levels gypsum cement, and lightweight concrete. This primer will improve spread rates and enhance the performance of the new adhesive. KPA 505 is a high solid, solvent free, acrylic primer that can be used over existing adhesive residue, including old cutback, and when properly applied, effectively creates a chemical barrier between existing adhesive residue and new adhesives used to install most floor covering products. KPA 505 is highly resistant to alkali and helps to protect the new adhesive from the negative effects of elevated pH.

Size	Trowel Sizes/Spread Rate
4 Gallon	350 sq. ft./gallon
1 Gallon	