

Contact Us

For more information, or to place an order, please contact your Kraus representative.



THE GOLD STANDARD IN UNDERLAYMENTS



dBcoverTM
LVT & Carpet Tile Underlay



dBcover™

LVT & Carpet Tile Underlay

- Pliable high density construction
- Smooths out minor sub-floor imperfections
- Sets a firm base to maintain floor stability over time
- Suitable for high traffic areas due to high compression resistance
- Quick and easy installation – saves times and money
- Hypoallergenic and odor free
- Contains no VOCs for optimal indoor air quality

dBcover CV Specifications

PROPERTIES	dBcover CV
Green Approval	No volatile organic compounds (VOCs) for optimal indoor air quality; Contains natural acoustic sand
Application	Residential Commercial
Thickness	1.5mm 0.059"
Density	59 lbs/ft ³ 950 kg/m ³
Content	100% virgin SBR rubber and natural acoustic sand
dB Rating (Impact Noise Insulation)	18 dB
Water Vapour Transmission (WVTR)	0.69 g/m ² . 24h (ASTM F 1249-06)
IFD (25%)	>120 kPa
Roll Width	3 ft 36"
Roll Length	33.3 ft 400"
Roll Weight	29 lbs
Full Roll	100 sq ft 11 sq yds
Color	Charcoal grey
Warranty	Limited lifetime warranty Transferable

