



ASPEN PEAK



luxury vinyl

SwiftClean



SwiftClean
Vinyl



SwiftClean is a technologically advanced, high performance, waterproof surface protector, chemically bound to the surface of every Enstyle Enhanced series product. Floors with SwiftClean are easier to maintain, helping to preserve the natural appearance of the floor for both residential and commercial installation.

PearlTouch™ Ceramic Bead

All Enstyle LVT products are coated with a durable ceramic bead finish. These tiny microscopic particles are embedded in the layers of the UV cured PearlTouch finish to help protect the surface finish from premature wear.

dBcover™ cv

Our premium high performance sound suppressant underlayment helps to smooth out minor subfloor imperfections while adding comfort and warmth to the floor.

FloorScore



Meets Indoor Air Quality Product Performance Standards for Building Interiors. CA Section 01350 and SCS EC10.3-2014.



Canyon View
KLTASP981RL



National Park
KLTASP471RL



Aster | KLTASP1804RL



Rowan | KLTASP1951RL



Boulder | KLTASP20421RL



Provincial | KLTASP2174RL



Arvada | KLTASP2257RL



True North | KLTASP461RL



= Colour is available in Circuit Flooring Collection

specifications

SUPPLIER	Kraus®					
CONSTRUCTION	PROFILE	WEAR LAYER	TYPE	VIRGIN PVC	FINISH	COLOUR VARIATION
Thickness 2 mm	 6"	12 mil	UV Cured Coating with Ceramic Bead	Yes	 4 sided micro-bevel	 Medium-High

carton configuration

Plank Size: 2 mm x 6" x Random Length (48", 30", 18") | Pcs/Carton: 24 | Packaging: 36 sq.ft./carton | 27.78 lbs/carton
Installation: Full spread Kraus Adhesive™ KPA 501 | Below, on or above ground level

27 year warranty

27 Year Residential Finish | 10 Year Medium Commercial

important information about vinyl flooring

Vinyl flooring is a beautiful reproduction of wood or stone and therefore variations in colour, tone and graining are to be expected. Please note that the display samples may not always be a true representation of the final product. For this reason, new and/or replacement flooring may not exactly match display samples and/or existing flooring. To ensure that the installation meets the manufacturers requirements please note that Kraus KPA 501 is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. Product image colours may vary due to print processes and monitor display settings. See krausflooring.com for latest specifications. 1612

