



CARLOTA PLANK

essential



luxury vinyl



SwiftClean

SwiftClean is a technologically advanced, high performance, waterproof surface protector, chemically bound to the surface of every Enstyle Essential series product. Floors with SwiftClean are easier to maintain, helping to preserve the natural appearance of the floor for both residential and commercial installation.

PearlTouch™ Ceramic Bead

All Enstyle LVT products are coated with a durable ceramic bead finish. These tiny microscopic particles are embedded in the layers of the UV cured PearlTouch finish to help protect the surface finish from premature wear.

dBcover cv

Our premium high performance sound suppressant underlayment helps to smooth out minor subfloor imperfections while adding comfort and warmth to the floor.



FloorScore

Meets Indoor Air Quality Product Performance Standards for Building Interiors. CA Section 01350 and SCS EC10.3-2014.



Pinar Oak | KLTECAR002



Trinidad Oak | KLTECAR011



Victoria Oak | KLTECAR172



Neuva Pine | KLTECAR193



Maribel Maple | KLTECAR121



Baracoa Birch | KLTECAR273



Manzanillo Maple | KLTECAR126



Westbury Hickory | KLTECAR514



Freeport Hickory | KLTECAR111



Hillcrest Ash | KLTECAR118

specifications

SUPPLIER		Kraus®			
CONSTRUCTION	PROFILE	WEAR LAYER	TYPE	VIRGIN PVC	FINISH
Thickness 2 mm	 6"	8 mil	UV Cured Coating with Ceramic Bead	Yes	 Square Edge

carton configuration

Plank Size: 2 mm x 6" x 36" | Pcs/Carton: 24 | Packaging: 36 sq. ft./carton
 Installation: Full spread Kraus Adhesive™ KPA 501 | Below, on or above ground level

20 year warranty

20 Year Residential Finish | 5 Year Medium Commercial

important information about vinyl flooring

Vinyl flooring is a beautiful reproduction of wood or stone and therefore variations in colour, tone and graining are to be expected. Please note that the display samples may not always be a true representation of the final product. For this reason, new and/or replacement flooring may not exactly match display samples and/or existing flooring. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus KPA 501 is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See krausflooring.com for latest specifications. 1703

