



Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



ASTM E648 Class I

This product has passed the standard test method for critical radiant flux of floor-covering systems using a radiant heat energy source and meets the standards as defined within ASTM E648.



Backing Performance

Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



Lifetime Warranties

- Commercial Wear
- Backing Performance



04 | Rock Gray



08 | Stormy Night



24 | Black Pepper



27 | Deep Ochre



37 | Coconut Shell



46 | Graphite

specifications

Supplier	Kraus®	
Fiber system	100% Solution dyed nylon	
Construction	Pattern scroll loop	
Backing system	EuroBac™ Plus Modular	
Pile weight	20 oz./y ²	678 g/m ²
Pile height	0.12"	3 mm
Gauge	1/12	47.2 rows/10 cm
Stitches	10.7 s.p.i.	42.0 stitches/10 cm
Density	6000	11.1 kilotex/cm ²
CRI/CCI air quality test	Green Label Plus	GLP2094
Environmental awareness	Eligible for any recycling program	
Recycled content	EuroBac Plus™ Modular Backing - min. 20% pre-consumer	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	ASTM E648 – Class I (direct glue) ASTM E662 – < 450 (flaming mode) DOC FF 1-70 - passes	
Colorfastness to light	5.0 (AATCC 16)	
Modular size (w x l)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton 39 lbs/carton	6 y ² /carton 32 cartons/pallet
Recommended adhesive	Kraus Premium Adhesive™ KPA-301	
Installation method	Monolithic, Quarter-Turn, Ashlar & Brick	
Lifetime Warranties (See full text for details)	Commercial Wear Backing Performance	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See krausflooring.com for latest specifications.

E&OE.

1706