



7070 WESTMINSTER



Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions warranty. Most spills can be easily removed through gentle blotting, allowing your carpet to remain beautiful in spite of life's little mishaps.



Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



Backing Performance

Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



10 Year Warranties

- Commercial Wear
- Backing Performance
- Stain Proof – No Exceptions™

7070 WESTMINSTER



01 | Cork



08 | Nickel



02 | Hazelnut



09 | Wrought Iron



04 | Wolf



07 | Midnight Blue

specifications

Supplier	Kraus®	
Fiber system	100% BCF Polypropylene	
Construction	Multi-level scroll loop	
Backing system	EuroBac™ Modular	
Pile weight	18 oz./y ²	610 g/m ²
Pile height	0.12"	3 mm
Gauge	1/12	47.2 rows/10 cm
Stitches	10.1 s.p.i.	47.2 stitches/10 cm
Density	6400	
CRI/CCI air quality test	Green Label Plus	
Environmental awareness	Eligible for any recycling program	
Recycled Content	EuroBac™ Modular backing - min. 20% pre-consumer	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	Radiant Panel ASTM E648 – Class I (direct glue) DOC FF 1-70 - passes	
Colorfastness to light	5.0 (AATCC 16)	
Modular size (w x l)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton 43 lbs/carton	6 y ² /carton 32 cartons/pallet
Recommended adhesive	Kraus Premium Adhesive™ KPA-301	
Installation method	Quarter-Turn	
10 Year Warranties (See full text for details)	Commercial Wear Backing Performance Stain Proof – No Exceptions™	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See krausflooring.com for latest specifications.

E&OE.

1603