

KRAUS PREMIUM ADHESIVE

carpet



KPA 290 Outdoor Adhesive

KPA 290 is specially formulated for the installation of synthetic turfs and grass carpets. KPA 290 is for indoor and outdoor applications where flammable products pose the risk of fire or where solvent fumes are unwanted. This adhesive provides an extremely tenacious, water resistant bond to concrete, asphalt paving surfaces and other common sub-floors. KPA 290 has a fast, aggressive tack and forms a long lasting bond.

Size	Trowel Sizes/Spread Rate
4 Gallon	Smooth backed carpets:
1 Gallon	3/32" x 3/32" x 3/32" V-notch, 125 sq. ft./gallon
	Rough backed carpets:
	1/8" x 1/8" x 1/8" U-notch, 100 sq. ft./gallon



KPA 298 Multi-Purpose Adhesive

KPA 298 Multi-Purpose Adhesive is a 0 VOC, non-staining, latex-based adhesive, designed for the installation of glue-down carpets and felt backed sheet vinyl. This non-flammable adhesive is protected by the CleanGuard® two-stage antimicrobial.

Size	Trowel Sizes/Spread Rate
4 Gallon	Woven polypropylene, Rough backed carpets:
1 Gallon	1/8" x 1/8" x 1/8" U-notch, 90-110 sq. ft./gallon
	Attached cushion, Smooth backed carpets:
	3/32" x 3/32" x 3/32" V-notch, 115-135 sq. ft./gallon
	Sheet vinyl:
	1/16" x 1/16" x 1/16" U-notch, 125-150 sq. ft./gallon



KPA 300 Premium Carpet Adhesive

Kraus KPA 300 Premium Carpet Adhesive is formulated for the installation of direct glue carpets and other types of floor covering. It is designed for direct glue downs of stiff and "boardy" carpets that have a tendency to curl or spring up after installation. KPA 300 adhesive remains tacky for an extended period, and has excellent rebonding capabilities. KPA 300 is a safe, light colored, low odor adhesive designed with the installer's needs in mind. KPA 300 is water resistant and non-flammable. This zero VOC adhesive is protected by the CleanGuard® two-stage antimicrobial.

Size	Trowel Sizes/Spread Rate
4 Gallon	Carpets:
	1/8" x 1/8" x 1/8" U-notch, 90-110 sq. ft./gallon
	Unitary, Double glue:
	1/8" x 1/8" x 1/16" U-notch, 45-55 sq. ft./gallon
	Sheet vinyl:
	1/16" x 1/16" x 1/16" Square notch, 125-150 sq. ft./gallon

KRAUS PREMIUM ADHESIVE

carpet



KPA 301 Carpet Tile Adhesive

Adhere PVC, urethane, bitumen, FiberCore™ and EuroBac™ backed carpet tiles. Tiles may be lifted and replaced without damage to tile or loss of bond. CRI Green Label Plus, zero VOC formula is protected by the BioFresh® two-stage antimicrobial.

Size	Trowel Sizes/Spread Rate
4 Gallon	PVC and Urethane-backed Carpet Tile:
1 Gallon	1/32" x 1/16" x 1/32" U-notch, 180-250 sq. ft./gallon
	Double glue pad to floor:
	1/16" x 1/16" x 1/16" U/Square notch, 125-150 sq. ft./gallon



KPA 302 Ultra Carpet Adhesive

Specifically formulated for the heaviest commercial applications. This ultra-strong, zero VOC adhesive is excellent for woven carpets, those with stiff unitary backings and attached cushion backings. KPA 302 Ultra Carpet Adhesive is THE professional's choice for double-glue and pattern matching applications. This formula has an extended working time and superior retack engineered to maximize installer efficiency. CRI Green Label Plus, zero VOC formula is protected by the BioFresh® two-stage antimicrobial.

Size	Trowel Sizes/Spread Rate
4 Gallon	Commercial Carpet Backings (except double glue):
1 Gallon	1/8" x 1/8" x 1/8" U/Square notch, 90-110 sq. ft./gallon
	Double glue carpet to pad:
	1/8" x 1/8" x 1/16" (Spacer) U-notch, 45-80 sq. ft./gallon



KPA 505 Floor Primer

KPA 505 primer is specially formulated as a primer coat over common sub-floors; concrete, APA approved plywood underlayment, floor patch, self-levels gypsum cement, and lightweight concrete. This primer will improve spread rates and enhance the performance of the new adhesive. KPA 505 is a high solid, solvent free, acrylic primer that can be used over existing adhesive residue, including old cutback, and when properly applied, effectively creates a chemical barrier between existing adhesive residue and new adhesives used to install most floor covering products. KPA 505 is highly resistant to alkali and helps to protect the new adhesive from the negative effects of elevated pH.

Size	Trowel Sizes/Spread Rate
4 Gallon	350 sq. ft./gallon
1 Gallon	