



# 7803 MATRIX



## Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions warranty. Most spills can be easily removed through gentle blotting, allowing your carpet to remain beautiful in spite of life's little mishaps.



## ASTM E648 Class I

This product has passed the standard test method for critical radiant flux of floor-covering systems using a radiant heat energy source and meets the standards as defined within ASTM E648.



## Backing Performance

Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



## 10 Year Warranties

- Stain Proof – No Exceptions™
- Commercial Wear
- Backing Performance



02 | Trinity



03 | Oracle



05 | Machine



06 | Trench Coat



07 | Prophecy



09 | Rebellion

## specifications

Supplier	Kraus®	
Fiber system	100% BCF Polypropylene	
Construction	Multi level loop	
Backing system	EuroBac™ Modular	
Pile weight	17 oz./y <sup>2</sup>	575 g/m <sup>2</sup>
Pile height	0.10"/0.22"	2.5 mm/5.5 mm
Gauge	5/64	50.4 rows/10 cm
Stitches	9 s.p.i.	25.4 stitches/10 cm
Density	4563	8.92 kilotex/cm <sup>2</sup>
CRI/CCI air quality test	Green Label Plus	
Environmental awareness	Eligible for any recycling program	
Recycled content	EuroBac™ Modular backing - min. 20% pre-consumer 100% PVC free	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	ASTM E648 – Class I (direct glue) DOC FF 1-70 - passes ASTM E662 – < 450 (flaming mode)	
Colorfastness to light	5.0 (AATCC 16)	
Modular size (w x l)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton 39 lbs/carton	5.98 y <sup>2</sup> /carton 32 cartons/pallet
Recommended adhesive	Kraus   Premium Adhesive™ KPA-301	
Installation method	Quarter-Turn and Ashlar	
10 Year Warranties (See full text for details)	Stain Proof – No Exceptions™ Commercial Wear Backing Performance	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See [krausflooring.com](http://krausflooring.com) for latest specifications.

E&OE.

1610