

# ACOUSTIC STEP

LVT/UNIVERSAL SOUND CONTROL UNDERLAYMENT

## APPLICATION

- RESIDENTIAL
- COMMERCIAL

## APPROVED FOR USE UNDER

- LVT/LVP
- LAMINATE
- ENGINEERED WOOD
- SOLID HARDWOOD
- WPC/SPC

## DIMENSIONS AND PACKAGING

Roll Size:	200/sf
Roll Width:	36"
Roll Weight:	30/lbs
Rolls/Pallet:	24
Pallets/Truck:	48 double stacked

## APPROVED SUBSTRATES

- Completely Cured Concrete
- Interior Plywood
- Cement Backer Units
- Properly prepared OSB

## SOUND RATINGS

- Luxury vinyl tiles and planks: IIC 73, STC 63
- Laminate and Wood Products: IIC 67, STC 63

## SUSTAINABILITY AND LEED

- Content: 100% Virgin Latex Rubber
- Recyclability: 100% Post Consumer
- Certification: Green Label Plus
- LEED Credit EQ 4.3: Low-Emitting Materials
- LEED Credit MRc5.1,5.2: Regional Content 20-30%
- LEED Credit IEQp3: Minimum Acoustical performance

## SPECIFICATIONS +/- 10%

PROPERTIES	UNDERLAYMENT
MATERIAL COMPOSITION	100% LATEX RUBBER
THICKNESS	1.8MM
DENSITY	25LB/FT3
COMPRESSION SET	ASTM D 1055-97 (22H, 70C) – 16%
INDENTATION	ASTM F1914 – 12%
SMOKE DENSITY	ASTM A662 – LESS THAN 89 MAX
FLAMMABILITY TEST	ASTM D 2859(DOC FF 1-70) – PASS
THERMAL RESISTANCE (R-VALUE)	0.205
ANTIMICROBIAL PROTECTION	YES
INDOOR AIR QUALITY	CRI CERTIFIED FOR LOW EMITTING MATERIALS
INSTALLATION METHODS	FLOAT, DOUBLE GLUE, NAIL DOWN, STAPLE
WARRANTY	LIMITED LIFETIME WARRANTY

PRESENTED BY  
 **KRAUS**<sup>®</sup>  
Premium Underlayment.™

